

CONSTRUCTION ACCESSORIES

CENTIPEDE SPACER WITH UPRIGHTS **DATASHEET**





DRUSPITZ-PLUS

FREE OF PVC

Application:

Plastic spacers for light reinforcement with very good concrete flow. Special foot spikes minimize contact with formwork. Vertical spikes on top prevent the reinforcement from slipping. Can be supplied without spikes on top.

Installation:

The DRUSPITZ is installed diagonally to the reinforcement. Additional information about the location and the installation spacing are contained in the DBV-data sheet.

Material:

Polyolefin (PO)

Free of PVC, CFC, HFC

Without substances of very high concern according to the candidate list of ECHA (REACH Regulation)

Packaging:

Free of halogen-containing compounds, azo dyes, flame retardants.

Order information:

Item	Concrete	Dimension	Pcs/	Pcs/	m/ Pallet
No.	cover mm	m	Bundle	Pallet	by 2m
DUPL15/100	15	1	40	3.520	7.040
DUPL20/100	20	1	40	3.520	7.040
DUPL25/100	25	1	40	3.520	7.040
DUPL30/100	30	1	40	3.200	6.400
DUPL35/100	35	1	40	3.200	6.400
DUPL40/100	40	1	40	3.200	6.400
DUPL45/100	45	1	40	3.200	6.400
DUPL50/100	50	1	40	3.200	6.400



Completely connected standarlength: 1m, 1,5m, 2m und2,5m

Approved according to DBV specification "Abstandhalter" DBV-c-L1/F/T/A

Important:

Guidelines for the choice and application of the spacers are managed by the following DVB data sheets. (German Society for Concrete and Construction Technology)

Spacers, support and concrete cover and reinforcement

Any other length (already connected) available!



SDG

Get in touch

HEAD OFFICE

21 Tullygoonigan Industrial Estate Moy Road Armagh BT61 8DR

Tel: +44 (0) 28 3752 8999

 ${\tt sdgconstructiontechnology.com}$

MONAGHAN OFFICE

Cornacrieve Emyvale Monaghan HY18 XY 46

Tel: + 353 (47) 87 295

Email: sales@sdg.ie