

CONSTRUCTION ACCESSORIES

# TOWER SPACER **DATASHEET**





#### 4-FUSS

#### **FREE OF PVC**

#### Application:

Robust spacer with large clamping zone for middle and heavy reinforcement. Ideal of application of the pre-cast industry and on the construction site.

#### Installation:

The 4-foot spacer are fixed at the intersections of the reinforcement. Additional information about the location and the installation spacing are contained in the DBV-data sheet.

#### Material:

- Polyolefin (PO)
- ☑ Free of PVC, CFC, HFC
- Without substances of very high concern according to the candidate list of ECHA (REACH Regulation)

#### Packaging:

Free of halogen-containing compounds, azo dyes, flame retardants

#### Order information:

Item-	Concrete	For iron Ø	Pcs/	Pcs/	Pcs/
No.	cover mm	mm	Bag	Big bag	Pallet
ATV20	20	6-20	500	2.000	12.000
ATV25	25	6-20	500	1.500	12.000
ATV30	30	6-20	250	1.500	12.000
ATV35	35	6-20	250	1.000	10.000
ATV40	40	6-20	250	1.000	10.000
ATV45	45	6-20	250	1.000	8.000
ATV50	50	6-20	125	500	7.500
ATV55	55	6-20	125	500	7.500





ATVF...- with flat foot spikes



ATVS...- with pointed foot spikes

#### Important:

The choice and use of spacers is regulated, amongst others, in:

- **図** DIN1045
- Data sheet of German Society for Concrete and Construction Technology: "Spacers", "Support", "Concrete cover and reinforcement"



## SDG

### Get in touch

#### HEAD OFFICE

21 Tullygoonigan Industrial Estate Moy Road Armagh BT61 8DR

**Tel:** +44 (0) 28 3752 8999

sdgconstructiontechnology.com

#### MONAGHAN OFFICE

Cornacrieve Emyvale Monaghan HY18 XY 46

**Tel:** + 353 (47) 87 295

Email: sales@sdg.ie