

CONSTRUCTION ACCESSORIES

TRIK TRAK DATASHEET






DRUNTERLEISTE

Application:

Linear spacer for the lower reinforcement.

The linear spacers with cut-outs at the side and very good concrete flow. The linear spacer with holes at the side and closed at the side are designed for use on a soft ground. The spacer must be turned upside down for this purpose.



Installation:

The DRUNTERLEISTE are installed diagonally to the reinforcement. Additional information about the location and the installation spacing are contained in the DBV-data sheet.

Material:

- Polyvinylchlorid (PVC)
- Free of CFC, HFC
- Without substances of very high concern according to the candidate list of ECHA (REACH Regulation)

Packaging:

Free of halogen-containing compounds, azo dyes, flame retardants

Order information - DRUNTERLEISTE

Item-	Concrete	Length	m/	m/
No.	cover mm	m	Bundle	Pallet
DL15/200	15	2	100	7.700
DL20/200	20	2	100	6.300
DL25/200	25	2	100	4.900
DL30/200	30	2	100	4.200
DL35/200	35	2	60	3.600
DL40/200	40	2	60	2.400
DL45/200	45	2	60	1.440
DL50/200	50	2	60	1.680
DL60/200	60	2	40	1.200
DL70/200	70	2	40	1.120
DL75/200	75	2	40	1.120
DL80/200	80	2	20	960

Other length available on request.

Approved according to DBV specification "Abstandhalter" DBV - c - L2/F



INFORMATION:



DRUNTERLEISTE

Order information - DRUNTERLEISTE VOLL

Item- No.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DLO25/200	25	2	100	4.900
DLO30/200	30	2	100	4.200
DLO35/200	35	2	60	3.600
DLO40/200	40	2	60	2.400
DLO45/200	45	2	60	1.440
DLO50/200	50	2	60	1.680
DLO60/200	60	2	40	1.200
DLO70/200	70	2	40	1.120



with holes at the side

Other length available on request.

Approved according to DBV specification "Abstandhalter" DBV - c - L2/F

Order information - DRUNTERLEISTE VOLL

Item- No.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DLV15/200	15	2	100	7.700
DLV20/200	20	2	100	6.300
DLV25/200	25	2	100	4.900
DLV30/200	30	2	100	4.200
DLV35/200	35	2	60	3.600
DLV40/200	40	2	60	2.400
DLV45/200	45	2	60	1.440
DLV50/200	50	2	60	1.680
DLV60/200	60	2	40	1.200
DLV70/200	70	2	40	1.120
DLV75/200	75	2	40	1.120
DLV80/200	80	2	20	960



closed at the side

Other length available on request.

Approved according to DBV specification "Abstandhalter" DBV - c - L2/F

Important:

The choice and use of spacers is regulated, amongst others, in:

• Data sheet of German Society for Concrete and Construction Technology: "Spacers", "Support", "Concrete cover and reinforcement"



SDG

Get in touch

HEAD OFFICE

21 Tullygoonigan Industrial Estate Moy Road Armagh BT61 8DR

Tel: +44 (0) 28 3752 8999

 ${\tt sdgconstruction} technology.com$

MONAGHAN OFFICE

Cornacrieve Emyvale Monaghan HY18 XY 46

Tel: + 353 (47) 87 295

Email: sales@sdg.ie